



**Item Number:** STL-2012CCD

**Price:** \$0.00

**Weight:** 22.000

**Series:** SpectraLite

**Operation:** Studio

**Display Size:** 12"

**Display Type:** Custom LED

**Scan Reversal:** Internal

**Standard Input:** Composite

**Brightness:** Standard

**Mirror Hood:** Standard Rigid

Trapezoidal Studio

**KG Weight:** 10

[Hi-res Image 1](#)

### **Spectra-Lite STL-2012CCD 12-inch Studio Prompter**

#### **QUALITY-BUILT IN THE USA...**

Spectra-Lite Model **STL-2012CCD** 12-inch LED Flat-panel On-Camera Prompter features a standard-sized rigid Trapezoidal Mirror/Hood Assembly with simple LED Tally and is suggested for studio operation. It is configured for a traditional style portable camera with ENG bayonet-mount (barrel) lens; a special configuration is available to accommodate portables mounted with an HD compact studio lens. Listec 12-inch displays are comfortably viewable up to 15 ft (4.6m) or more from the presenter.

#### **FEATURES:**

Listec Spectra-Lite LED displays feature the latest flat-panel technology and are a natural step up from traditional monitor-based and LCD prompters. They provide a sharp, vivid image without compromise at very attractive pricing and are in use by broadcasters, corporations, educational facilities and institutions around the World. As an added bonus, Spectra-Lite 12-inch prompters feature standard brightness and contrast that some would call "high bright". While composite video inputs are standard, VGA and SDI connectors are optionally available. Supplied with Listec's easy-mount hardware, the STL-2012CCD will provide many years of trouble-free service.

#### **INCLUDES:**

- 12-inch high quality LED Display with vandal shield for flat-panel protection
- Standard-sized Studio Trapezoidal Mirror/Hood Assembly with simple LED Tally Light. (Will accommodate lens focal length of 4.5mm or longer.)

- Sliding EFP Balance Plate
- Camera Riser with sliding top platform and 3"/4"/5" incremental height settings

***Options/Accessories To Consider:***

**BT-3509-ASSY** Factory installed Internal SensaTally featuring auto-sensing from light source and brightness control. Positioned inside center-front of display case

**BT-3510-ASSY** Factory installed External SensaTally

**LM-VGA** Factory installed DB 15-Pin VGA connector

**LM-SDI** Factory installed SDI connector

**A-1215-XX** Sliding Rear EFP Counterbalance weight - *refer to On-camera Accessories for more information*  
 Consider for cameras under 17 lb (7.7kg) operating *without* a studio viewfinder  
 Consider for cameras under 14 lb (6.4) operating *with* a studio viewfinder

**CCDW** Wide-angle configuration for portable style camera with compact HD studio lens

**A-6WIN/6A** Windows InstantEdit Prompting System

**SPECIFICATIONS**

STL-2012CCD Prompter Weight, less counterbalance: 24 lb (10.9kg)

***12-inch Spectra-Lite Flat Panel:***

- Vandal Shield for LED protection
- 2 X looping BNC Composite Inputs with 75-Ohm termination switch
- Remote Control for selection of all settings from easy-to-read menus
- Image Reversal by menu command
- Standard Brightness: 600 nits
- Contrast: 1000:1
- Resolution: SVGA 800X600
- Power inputs: 12VDC ±10% by means of external universal A/C Adapter
- Power draw: Under 20W at maximum brightness
- Backlight life: 45,000 hours
- Viewing angle: 178° horizontal
- Operating temperature: -22°F—158°F/-30°C—70°C
- TV Standard: NTSC/PAL/SECAM
- RoHS compliant