



Item Number: STL-2012P

Price: \$0.00

Weight: 15.000

Series: SpectraLite

Operation: Studio/Field OB

Display Size: 12"

Display Type: Custom LED

Scan Reversal: Internal

Standard Input: Composite

Brightness: Standard

Mirror Hood: Standard Fold-down
Soft

KG Weight: 6.8

Spectra-Lite STL-2012P 12-inch Field OB and Studio Prompter

Quality-built in the USA....

Spectra-Lite Model **STL-2012P** 12-inch LED Flat-panel On-Camera Prompter features a standard-sized Fold-down Mirror/Soft Hood and is suggested for OB field or studio operation. It is configured for traditional style portable cameras with ENG bayonet-mount (barrel) lens and is comfortably viewable up to 15 ft (4.6m) or more from the presenter. Its light weight makes the STL-2012P especially ideal for small studios, location shooting and mounting on camera jibs.

FEATURES:

Listec Spectra-Lite LED displays feature the latest flat-panel technology and are a natural step up from traditional monitor-based and LCD prompters. They provide a sharp, vivid image without compromise at very attractive pricing and are in use by broadcasters, corporations, educational facilities and institutions around the World. As an added bonus, Spectra-Lite 12-inch prompters feature standard brightness and contrast that some would call "high bright". While composite video inputs are standard, VGA and SDI connectors are optionally available. Supplied with Listec's easy-mount hardware, Spectra-Lite On-camera Prompters are lightweight, yet rugged enough to serve double duty for both in-house and outside broadcast field operation.

INCLUDES:

- 12-inch high quality LED Display with vandal shield for flat-panel protection
- Standard-sized Fold-down Mirror/Soft Hood Assembly
- Sliding ENG Balance Plate

Options/Accessories To Consider:

- **LM-VGA** Factory installed Add-on, DB 15-Pin VGA connector
- **LM-SDI** Factory installed Add-on, SDI connector
- **B-20157P/MFA-V** Wide-angle Trapezoidal Fold-down Mirror/Soft Hood Assembly to accommodate lens focal length of 4.5mm or longer
- **BT-3509-ASSY** Factory installed Internal SensaTally featuring auto-sensing from light source and brightness control. Positioned inside center-front of display case.
- **BIL-EA75-12** Direct Battery Input (4-pin XLR-M), 9-18VDC @ 5.6A, 67.25W
- **B-3451** Offset Camera Riser to facilitate lens cable clearance and position the camera lens center to the mirror and as far inside the hood as possible. Suggested for low-profile cameras.
- **A-10XX-A** Sliding Rear ENG Counterbalance weight. Consider for cameras under 17 lb (7.7kg) *Refer to On-camera Accessories for additional information.*
- **TC-TS2012P** Transit Case featuring retractable handle, casters, combination lock and shipping tab
- **A-6WIN/6A** Windows InstantEdit Prompting System

SPECIFICATIONS:

STL-2012P Prompter Weight, less counterbalance: 15 lbs (6.8kg)

12-inch Spectra-Lite Flat Panel:

- Vandal Shield for LED protection
- 2 X looping BNC Composite Inputs with 75-Ohm termination switch
- Remote Control for selection of all settings from easy-to-read menus
- Image Reversal by menu command
- Standard Brightness: 600 nits
- Contrast: 1000:1
- Resolution: 800X600
- Power inputs: 12VDC $\pm 10\%$ by means of external universal A/C Adapter
- Power draw: Under 20W at maximum brightness

- Backlight life: 45,000 hours
- Viewing angle: 178° horizontal
- Operating temperature: -22°F—158°F/-30°C—70°C
- TV Standard: NTSC/PAL/SECAM
- RoHS compliant