



Item Number: STL-2015PT

Price: \$0.00

Weight: 18.000

Series: SpectraLite

Operation: Studio/Field OB

Display Size: 15"

Display Type: Custom LED

Scan Reversal: Internal

Standard Input: Composite

Brightness: Standard

Mirror Hood: Trapezoidal Fold-down Soft

KG Weight: 8.2

Spectra-Lite STL-2015PT 15-inch Compact Studio Prompter

QUALITY-BUILT IN THE USA...

Spectra-Lite Model **STL-2015PT** is a 15-inch LED On-Camera Prompter ideally suited to in-house production. Its compact and lightweight design make it perfect for small studios and robotic applications where a 15-inch display is preferred. Featuring a Wide-angle Trapezoidal Fold-down Mirror/Soft Hood and Listec's easy-mount support system, Model STL-2015PT is readable to 20 ft (6.1m) or more from the presenter.

FEATURES:

Listec Spectra-Lite Displays feature the latest LED flat-panel technology and are a natural step up from traditional monitor-based and LCD prompters. They provide a sharp, vivid image without compromise at very attractive pricing and are in use by broadcasters, corporations, educational facilities and institutions around the World. Spectra-Lite Displays are quality-built in the USA by Listec and feature standard brightness and high contrast. While composite video inputs are standard, VGA and SDI connectors are optionally available.

INCLUDES:

15-inch Custom LED Display with vandal shield for flat-panel protection

Wide-angle Trapezoidal Fold-down Mirror/Soft Hood Assembly to accommodate lens focal length to 4.5mm or longer.

Sliding Mid-sized EFP Balance Plate

Options/Accessories To Consider:

- **LM-VGA** Factory installed DB 15-Pin VGA connector
- **LM-SDI** Factory installed SDI connector

- **BT-3509-ASSY** Factory installed Internal SensaTally featuring auto-sensing from light source and brightness control. Positioned inside center-front of display case.
- **BIL-EA75-12** Direct Battery Input (4-pin XLR-M), 9-18VDC @ 5.6A, 67.25W
- **B-3451** Offset Camera Riser to facilitate lens cable clearance and position the camera lens center to the mirror and as far inside the hood as possible. Suggested low-profile cameras.
- **A-1215-XX** Sliding Rear EFP Counterbalance weight. Consider for cameras under 24 lb (10.9kg) - *refer to On Camera Accessories for more information*
- **TC-TS2015PT** Transit Case featuring retractable handle, casters, combination lock and shipping tab.

SPECIFICATIONS:

STL-2015PT Prompter Weight, less counterbalance: 19 lb (8.6kg)

15-inch Spectra-Lite LED Flat Panel:

- Vandal Shield for LED protection
- 2 X looping BNC Composite Inputs with 75-Ohm termination switch
- Remote Control for selection of all settings from easy-to-read menus
- Image Reversal by menu command
- Standard Brightness: 400 nits
- Contrast: 700:1
- Resolution: XGA 1024X768
- Power inputs: 12VDC \pm 10% by means of external universal A/C Adapter
- Power draw: Under 30W at maximum brightness
- Backlight life: 45,000 hours
- Viewing angle: 160° horizontal
- Operating temperature: -22°F—158°F/-30°C—70°C
- TV Standard: NTSC/PAL/SECAM
- RoHS complaint